
	MANUFACTURER	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE	NOTIFIED BODY	CONFORMITY ASSESSMENT SYSTEM			YEAR OF INTRODUCTION	
	TERMA ARTUR DARIUSZ I HELENA SZYMANIUK SPÓŁKA JAWNA UL. POZNAŃSKA 42A 76-200 ŚLUPSK	EXTERNAL WINDOWS AND DOORS WITHOUT RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS VEKASLIDE 82 SYSTEM	№ 0757 ift ROSENHEIM GMBH THEODOR-GIETL-STR. 7-9 83026 ROSENHEIM	3			14	
DECLARATION OF PERFORMANCE NO. 9/2015/O								
INTENDED USE	INTENDER FOR THE USE IN PREMISES OF RESIDENTIAL AND PUBLIC BUILDINGS							
IDENTIFICATION OF THE CONSTRUCTION PRODUCT	ON THE BASIS OF THE LABEL WITH THE SERIAL NUMBER							
DECLARED PERFORMANCE	BASE ON THE HARMONISED TECHNICAL SPECIFICATION EN 14351-1+A1:2010							
PRODUCT CODE	RESISTANCE TO WIND LOAD – DEFLECTION OF THE FRAME	RESISTANCE TO WIND LOAD – TEST PRESSURE	WATERTIGHTNESS - NON-SHIELDED (A)	OPERATING FORCES	MECHANICAL STRENGTH	LOAD BEARING CAPACITY OF SAFETY DEVICES	AIR PERMEABILITY	DANGEROUS SUBSTANCES
HS WINDOWS AND BALCONY DOORS OF DIMENSIONS NOT EXCEEDING 1983X2183 mm	C/B	2	7A	1	4	350 N	Class 4	Nie zawiera
LARGE SIZE HS BALCONY DOORS - MAXIMUM LIMIT SIZE 2483X2583 mm	C/B	1	3A	1	4	350 N	Class 4	Nie zawiera

THERMAL TRANSMITTANCE U <sub>w</sub> FOR THE REFERENCE WINDOW*				ACOUSTIC PERFORMANCE**				
U <sub>s</sub> THERMAL TRANSMITTANCE OF THE FRAME (W/m <sup>2</sup> K)	Ψ OF THE SPACER (W/m <sup>2</sup> K)			R <sub>w</sub> AIRBORNE SOUND INSULATION OF THE INSULATED GLASS PANEL (dB)	AIRBORNE SOUND INSULATION R <sub>w</sub> (dB) FOR THE TOTAL SURFACE AREA OF THE WINDOW (F)			F<4.6m <sup>2</sup>
	Ψ=0.07	Ψ=0.04	Ψ=0.032		F<2.7m <sup>2</sup>	2.7m <sup>2</sup> <F<3.6m <sup>2</sup>	3.6m <sup>2</sup> <F<4.6m <sup>2</sup>	
1,1	1,2	1,2	1,1	27	30	29	28	27
1,0	1,2	1,1	1,1	28	31	30	29	28
0,9	1,1	1,0	1,0	29	32	31	30	29
0,8	1,0	1,0	0,9	30	33	32	31	30
0,7	1,0	0,9	0,9	32	34	33	32	31
0,6	0,9	0,8	0,8	34	35	34	33	32
0,5	0,83	0,76	0,74	36	36	35	34	33

\* Frame with the size of 1230 x 1480 mm with various glazing and spacers

\*\* Values determined in accordance with section B.3 of the Annex B to EN 14351-1+A1:2010 standard for frames with various types of glazing

NPD – no performance determined

  
mgr inż. Marek Pręczek  
Signed on behalf of the manufacturer  
Ślupsk, 01/09/2015