



®

MANUFACTURER
TERMA ARTUR DARIUSZ
I HELENA SZYMANIUK
SPÓŁKA JAWNA
UL. POZNAŃSKA 42A
76-200 ŚLUPSK

UNIQUE IDENTIFICATION CODE OF THE
PRODUCT - TYPE
EXTERNAL WINDOWS AND DOORS
WITHOUT RESISTANCE TO FIRE AND/OR SMOKE
LEAKAGE CHARACTERISTICS
IDEAL HST 85 SYSTEM

NOTIFIED BODY
№ 0757
ifc ROSENHEIM GMBH
THEODOR-GIETL-STR. 7-9
83026 ROSENHEIM

CONFORMITY
ASSESSMENT
SYSTEM
3



YEAR OF INTRODUCTION
14

DECLARATION OF PERFORMANCE NO. 4/2015/O

INTENDER FOR THE USE IN PREMISES OF RESIDENTIAL AND PUBLIC BUILDINGS

INTENDED USE
IDENTIFICATION OF THE CONSTRUCTION
PRODUCT

ON THE BASIS OF THE LABEL WITH THE SERIAL NUMBER

DECLARED PERFORMANCE

BASE ON THE HARMONISED TECHNICAL SPECIFICATION EN 14351-1+A1:2010

PRODUCT CODE	RESISTANCE TO WIND LOAD - DEFLECTION OF THE FRAME	RESISTANCE TO WIND LOAD - TEST PRESSURE	WATERTIGHTNESS - NON-SHIELDED (A)	OPERATING FORCES	MECHANICAL STRENGTH	LOAD BEARING CAPACITY OF SAFETY DEVICES	AIR PERMEABILITY	DANGEROUS SUBSTANCES
SINGLE LEAF HS DOORS	C/B	2/4	9A	1	4	350 N	Class 4	None
SINGLE LEAF HS DOORS WITH ALUSKIN	C/B	3/5	E 750	1	4	350 N	Class 4	None
DOUBLE LEAF HS DOORS	C	1	9A	1	4	350 N	Class 4	None
DOUBLE LEAF HS DOORS WITH ALUSKIN	C/B	1	9A	1	4	350 N	Class 4	None
LEAF HS DOORS WITH MAXIMUM FOUR SASHES	C/B	1	9A	1	4	350 N	Class 4	None
LEAF HS DOORS WITH MAXIMUM FOUR SASHES WITH ALUSKIN	C/B	1	9A	1	4	350 N	Class 4	None

THERMAL TRANSMITTANCE U FOR THE REFERENCE WINDOW*				ACOUSTIC PERFORMANCE**				
U THERMAL TRANSMITTANCE OF § THE PANE (W/m²K)	W OF THE SPACER (W/m²K)			R _w AIRBORNE SOUND INSULATION OF THE INSULATED GLASS PANEL (dB)	AIRBORNE SOUND INSULATION R _y (dB) FOR THE TOTAL SURFACE AREA OF THE WINDOW (F)			
	W=0.07	W=0.04	W=0.032		F<2.7m²	2.7m²<F<3.6m²	3.6m²<F<4.6m²	F>4.6m²
1,1	1,2	1,2	1,1	27	30	29		28
1,0	1,2	1,1	1,1	28	31	30		29
0,9	1,1	1,0	1,0	29	32	31		30
0,8	1,0	1,0	0,9	30	33	32		31
0,7	1,0	0,9	0,9	32	34	33		32
0,6	0,9	0,8	0,8	34	35	34		33
0,5	0,83	0,76	0,74	36	36	35		34

* Frame with the size of 1230 x 1480 mm with various glazing and spacers

** Values determined in accordance with section B.3 of the Annex B to EN 14351-1+A1:2010 standard for frames with various types of glazing

NPD - no performance determined

DYREKTOR
mgr inż. Marcin Fryczek
Signed on behalf of the manufacturer
Ślupsk, 01/09/2015